

Panel PC

P10R (Linux version)


- Equipped with 4-core ARM architecture A55 processor and Debian 11 operating system
- Full 10.1-inch HD display, the IP65-rated front panel protects against water and dust ingress
- Fanless design, excellent in heat dissipation and strong stability performance
- Wide voltage and temperature working performance, perfect for 24/7 use in all weather conditions
- Rich interfaces, including multiple USB/RS232/LAN/HDMI and other I/O ports, easily meet various scenario requirements
- MiniPCIE slot, can be expanded with communication modules, solid-state drives and other peripherals
- Support 802.11b/g/n/ac protocol, dual Wi-Fi antennas and Bluetooth 5.0
- Standard PPC mounting hook component, easy to install and supports various installation methods such as embedded and wall-mounted

expansion



extensions

affecting reliability



Panel PC P10R

INERU99ed

Specifications



RK3568 Quad core



Operating System

Debian 11



Memory

RAM: 4GB onboard ROM: 64GB



Display

Type: LCD Size: 10.1 inch 16:10 Resolution: 800×1280 Brightness:700 cd/m²



Touch Pannel



Dimension/Weight

257.2*170*45.95mm 1.2kg



Internet

Dual-band WiFi/BT5.0



Standard USB-A USB3.0*1 + USB3.0 *1 OTG +

USB2.0*2 Power interface

DC IN 12V-24V Power connector *1

Standard Earphone Jack *1

RJ45 *1

DB9 PORT RS232 *2

(Mainboard switchable to RS485:

RS485 *1, RS232 *1)

HDMI *1



Front panel IP65



Working temperature: -20 °C to 60 °C Storage temperature: -30 °C to 70 °C Humidity: 95% Non-Condensing Electrostatic discharge:

± 15kV air discharge

± 8kV contact discharge



Adapter


AC100V ~ 240V、50Hz/60Hz output DC 12V/4A













* The technical specifications of this product are subject to change without prior notice



