


Panel PC

- Powered by a quad-core ARM processor with Android 12 OS;
- 17-inch 4:3 industrial display, compatible with professional applications;
- Wi-Fi 5, BT 5.0; Supports 4G network connectivity;
- Multiple interfaces options: USB, RS232, RJ45, HDMI, and audio ports;
- Standard PPC hook assembly accessory;
- VESA holes for wall and desktop mounting;
- Wide voltage input: 12V to 24V;
- Operational temperature range: -30°C to 70°C;
- Anti-electromagnetic interference; IP65-rated front panel.



Quad-core ARM processor



Android 12



17-inch 4:3 screen




500cd/m² Brightness



Dual-band WIFI




Running 24/7 without affecting reliability



Rich interface extensions



IP65 Front Panel





Panel PC P17R

Specifications



Quad-core ARM processor



Android 12



RAM 4GB ROM 64GB

Display

Type: LCD Size: 17 inch 4:3 Resolution:1280×1024 Brightness: 500cd/m²



10-point capacitive touch



401*332*57 mm



WIFI 802.11a/b/g/n/ac Frequency 2.4G+5.8G dual band WIFI



BT 5.0



Optional: M. 2 interfaces, USB&PCIE signal compatibility

Black



Type A USB: USB3.0 *1, USB3.0 *1 OTG USB2.0 *2 DC IN 12V-24V Power connector *1 3.5mm Standard Earphone Jack *1 RJ45 *1 (10M/100M/1000M adaptive) DB9 PORT RS232 *2 HDMI*1



Rugged Features

Working temperature: -30 °C to 70 °C Storage temperature: -30 °C to 70 °C Humidity: 95% Non-Condensing



Output Certification


IP65 Front panel








Panel PC P17R Product Six Views














Accessories(Standard)







antenna *2 2.4-2.5/5.15-5.85GHZ 2dBi (SMA)

* The technical specifications of this product are subject to change without prior notice



© Tel: 400-830-4882

www.onerugged.com

□ inquiry@onerugged.com

© Emdoor Building, No.8 Guangke lst Road, Pingshan District, Shenzhen